

## Manual Sliding Gates



## Cantilever Sliding Gates

If space is an issue or the driveway behind the gates is on a steep incline, a better option would be a sliding gate. Sliding gates are also very popular in a commercial environment. Our gates are compliant straight from our factory and are ready to bolt down and connect power too. You can install the gate and have peace of mind knowing that they comply to the latest standards. They are in short easy to install and use. We deliver our gates with our Hi-Ab lorry.

### 9000M

- The 9000M Cantilever Manual Sliding Gate is a cost effective, low maintenance and effective way of manually controlling access to unauthorised areas.
- The internal roller mechanism ensures a smooth and consistent ease of operation providing a durable and efficient service for years to come.
- Optional spikes line the top of the gate to deter intruders. The 6mm wall thickness, evenly spaced individual aluminium bars fitted as standard, further add to the sturdy appearance. A heavy duty locking mechanism as standard will give you peace of mind in the knowledge that the lock is as tough and secure as the gate.
- The manual gates share the same flexibility as the automatic range offering a vast choice of infills such as palisade, mesh and custom infills, which can be easily applied to the gate frame if the standard tubular bar is not suitable for the environment.
- The gate is delivered as a complete unit and lowered on to pre-installed concrete plinths.



**Optional extras:**  
Razor Wire Extensions  
Electric Fence  
Anti-Climb Spikes  
Timber Infills  
Louvre Infills

# Manual Sliding Gates



Maximum Span	12 Metres
Opening / Closing Time	N/A
Drive method	Manual
Power Supply	N/A
Finish	Aluminium Powder Coated / 2K PU Finish
Safety Features	N/A
Infill's	Mesh / Tube / Palisade / Louvre
Cycles	100% Continuous Duty Cycle Rating
Control Panel	N/A
Max Height	2.4m (max width 12.0m) 3.0m (max width 10.0m)
Auxiliary Power	N/A
Infill's Dimensions	Std - 30mm round bar x 6mm wall thickness
Ambient Humidity	-10 ~ 60 Degrees Centigrade
Control Panel IP Rating	N/A
Fixings	M16 / M20 Anchor Shield Bolts Included
Override	Manual operation / Dead Man Key Switch

